Bunker Silage Storage Leachate and Runoff Management

Eric Cooley, UW Discovery Farms

Aaron Wunderlin, UW Discovery Farms
Dr. Becky Larson, Assistant Professor UW-Madison
Mike Holly, PhD Student UW-Madison







Feed Storage Leachate Studies

UW Biological Systems Engineering (Dr. Rebecca Larson and Michael Holly)

- 3 locations: Arlington Agricultural Research Station, Dairy Forage Research Center and private dairy bunker
- Total combined runoff monitored
- Monitored October 2011 to October 2012 (no wintertime monitoring)
- Discrete sample protocol to characterize individual storms

<u>UW Discovery Farms</u>

- 3 locations: 3 private dairy bunkers
- Both leachate collection system and overflow to VTA monitored separately
- Monitored October 2012 to December 2014 (with wintertime monitoring)
- Discrete and composite sample protocol to focus on annual loading trends







Leachate










Leachate Production Based on Dry Matter Content




(Haigh, 1999)







Timing of Leachate Production



Mc Donald 1981, Referencing Bastiman 1976







Runoff









What is in leachate and runoff?


Constituent	Liquid Dairy Manure ¹	Leachate ²	Feed Storage Runoff
Dry Matter	5%	5% (2-10%)	0 - 5%
Total N (mg/L)	2,600	1,500-4,400	20 – 1,400
P (mg/L)	1,100	300-600	8 - 660
K (mg/L)	2,500	3,400-5,200	n/a
рН	7.4	3.6-5.5	4 - 7
BOD (mg/L)	5,000-10,000	12,000-90,000	500 - 61,000







Edge of Field vs Feed Storage Water Comparison










Edge of Field vs Feed Storage Phosphorus Comparison










Edge of Field vs Feed Storage Nitrogen Comparison









Collection System Design

Current System Design (NRCS Code 629)

- Capture all leachate
- Capture 1st flush runoff
 - Engineered based on urban runoff system design
 - Percent collected based on feed storage area and VTA sizing
- 25-year/24-hour storm diversion

Future system design

- EPA has expressed concerns to DNR about current operation/design of VTAs meeting WPDES "no discharge" requirements
- More efficient alternative systems?







Collection System Design

<u>Objectives</u>

- Comply with "no discharge" requirement while minimizing storage and handling costs
 - Total containment up to a 25-year, 24-hour storm event vs.
 - Collect high concentration liquid
 - Modify VTA design/operation of VTA, if possible








Collection Designs are Numerous







Nutrient Collection










Does a First-Flush Exist?




(Taebi & Droste, 2004)







Normalized Phosphorus Data










Normalized Phosphorus Data










Normalized Phosphorus Data









? 1st Flush?

First flush prevalence compared to urban definitions (all farm data combined):

Strict (80/30) ^a		Moderate (40/20) ^b		
TP	TKN	TP	TKN	
0	0	3	3	
0%	0%	3%	3%	

^a Bertrand-Krajewski et al (1998) ^b Deletic (1998)

TPn = 116 TKNn = 118







Why doesn't first flush exist?


Runoff concentrations are highly dependent on flow

Influenced by contact and residence time with stored feed, feed litter, and spoilage piles



































All constituents reacted similarly











Constituent Correlations

 All constituents (TP, TDP, TKN, Conductivity, COD, TS) were statistically correlated EXCEPT pH which was least correlated and inversely proportional

 This would allow for real-time monitoring of a constituent to determine collection or no collection







Nutrient Speciation

		TP (lbs)	TDP	TKN (lbs)	Ammonia
Farm A	L1	1,204	93%	4,412	37%
	L2	1,106	89%	4,550	24%
Farm B	L3	283	91%	1,029	32%
	L4	1,480	85%	5,893	23%
Farm C	L5	13	88%	78	28%
	L6	71	87%	374	23%







Annual Loading

<u>Investigated</u>

- Timing of loading
- Load collected vs. load to VTA
- Volume collected vs. load collected

Seasonality and a few events


- Snowmelt
- Big rains
- Filling







Total P Loading










Total P Loading










Design Concepts




Time








Collection Design Comparisons












Conductivity Metering









Collection Design Recommendations

- First flush rarely exists!
 - Not the greatest load per volume
 - Collect low flow only
 - Or continuous throughout

Additional collection within 2 weeks of filling







Minimizing Runoff Concentrations

- Protect from water
 - Cover when filling if rain is forecast
 - Cover/wrap side walls
 - Cover and seal edges
 - Divert clean water away
 - Minimize exposure when feeding
- Clean pad (remove litter) particularly if rain event is forecast
- Cover spoilage and litter piles until removal







Litter and Spoilage













Ineffective covering









Key Filter Strip Design Components

- Spreader at point of discharge to filter strip
- Ensure even application across filter strip
 - Irrigation pods
 - Grade evenly (difficult to achieve, need to supervise)
 - Rock checks for spreading
 - Impermeable membrane
 - 2-4 inch round stone
 - Every 100 feet of length







Spreader at Discharge











Ineffective Rock Check









To be continued...

Other analysis being conducted

- Recommended loading: filter strips (Larson)
- Timing and variation of constituent loss
- Effect of feed volume and area covered

Study reports

- Technical report (March)
- Fact sheets (April)
- Extension publications (December)







Thank You!

Questions/Comments

http://www.uwdiscoveryfarms.org

Eric Cooley

Mobile: (608) 235-5259 etcooley@wisc.edu

Engineering/Design:

Dr. Becky Larson (608) 890-3171 ralarson2@wisc.edu





